

106 Twin Terrace Way Spring Branch, Texas 78070-6288

Phone: 830-438-3808 Email: sales@trans-heat.com Web: trans-heat.com

Romans 10:11 For whosoever believes on Him shall not be ashamed.

ACCESSOFIES



The SCK-2 power termination kit is for terminating self-regulating or constant wattage heater cables into a NEMA 4X enclosure (customer supplied) through a CGB fitting. The kit comes with heat shrink tubing to isolate each conductor including the ground braid. The SCK-2 is ideal for use in roof and gutter applications and comes with wire nuts for connecting to service leads.

Material	Nylon Polifil 627
Melting Point	400°F
Tensile Strength	6,800 PSI
Izod Impact Strength	Ft./Lb./Inch Notch 16
Rockwell Hardness	R Scale 105
Operating Temperature Range	-60°F to 380°F
Hub Size	1" NPT
Dimensions	6-13/16″Lx4″Wx3-9/32″D
CGB Fitting	Nylon 6/6 (212°F)
Bushing	Buna-N (212°F)
5	*



| Second Circuit (Optional)

CONFIGURATIONS

Example Configuration	RG-PK-SR	
Туре	Cable Type	Weight
SCK-2 (Power Kit)	SR=Self-Regulating	5 oz.
RG-PK (Power Kit)	CW=Constant Watt	1.0 Lb.
RG-SK (Splice Kit)		1.0 Lb.
RG-TK (Tee Kit)		1.0 Lb.
Note: Different bushing used for constant wattage cables.		